

SGG HORIZON

SGG HORIZON GREEN (SCN 445)

ADVANCED SOLAR CONTROL GLASS

OFFERING CLEAR VISION AND OCCUPANT PRIVACY



SGG HORIZON GREEN (SCN 445)

SGG Horizon is an advanced coated glass manufactured by the state-of-art magnetron sputtering process under vacuum conditions. SGG Horizon Green is an energy efficient glass that comes with a green tinted base. It provides extremely low internal reflections enabling clear vision during the day as well as night .

FEATURES

SGG Horizon Green is a unique product that offers best of solar control with minimum internal reflections enabling the occupant to better visual connect even during night

- Low internal reflections resulting in excellent night view
- Optimum Light Transmission
- Green tinted base
- Solar control
- Thermal insulation
- UV protection



THICKNESSES

- Standard thicknesses of 4mm, 5mm and 6mm are available
- 8mm available on special request



PROCESSING

SGG Horizon Green is suited for use in both single and double glazed units. To obtain its performance and aesthetics, SGG Horizon Green can be

- Tempered /Heat Strengthened
- Assembled into an IGU
- Laminated units
- Bent units



APPLICATIONS

- Windows
- Skylights
- Structural glazing
- Façade glazing
- Bolted systems
- Curtain wall glazing
- Fenestration applications.



SUSTAINABILITY

As the world leader in glass manufacturing for the construction market, Saint-Gobain worldwide is committed to provide innovative solutions.

SGG Horizon Green can add value in occupant comfort, energy efficiency and is a sustainable product with recycled content. This will suit the requirements of green building labelling systems like:



SGG Horizon Green products conform to:



SAINT-GOBAIN GUARANTEE

654 PPI

PURITY KA
PERFECT
MEASURE.



TO KNOW MORE ON PRODUCT SELECTION, REACH OUT TO US HERE

PRODUCT PERFORMANCE

SGG HORIZON GREEN (SCN 445)

SGU: 6 mm Coated Glass (Coating Face 2)

DGU: 6 mm Coated Glass (Coating Face 2) – 12 mm Air Gap – 6 mm Clear Glass

LIGHT FACTORS

TYPE	TRANSMISSION (%)	REFLECTION (%)	
		EXTERNAL	INTERNAL
SGU	37	17	4
DGU	34	18	11

Luminous factors calculated with CIE (15-2004) D65 lighting Conditions

ENERGY FACTORS

(EN) SOLAR FACTOR	SHADING CO-EFFICIENT	(EN) U-VALUE
SHGC / SF	SC	(W/Sq.m K)
0.36	0.41	4.9
0.27	0.31	2.5

Solar Transmission Characteristics as per EN 410
Thermal Conductance as per EN 673

ENERGY FACTORS

(NRFC) SOLAR FACTOR	SHADING CO-EFFICIENT	(NRFC) U-VALUE SUMMER
SHGC / SF	SC	(W/Sq.m K)
0.39	0.45	4.3
0.29	0.33	2.5

Solar Transmission Characteristics as per NFRC 200/300
Thermal Conductance as per NFRC 100

SGG HORIZON GREEN (SCN 445)

SGG HORIZON GREEN UNDER SUNNY CONDITIONS



SGG HORIZON GREEN UNDER OVERCAST CONDITIONS

